

Customer _____ Tel _____ Order _____ Quote _____ Date _____
 Address _____ Mobile _____ Project Name _____
 _____ Email _____ Project Location _____

ID	Location	Blind or Recess	Width (X)	Drop (Y)	Fabric	Hardware Colour	Restraint Options	Fixings	Handle/Hold Down	Qty
1		Blind Recess				White Beige Graphite	Free Hanging Guide wire Chrome Dome Nickel Dome Chrome Flush Black Flush Nickel Flush	Top Face	No handle/Face Chrome /Face Chrome/Bottom Nickel/Face Nickel/Bottom	
2		Blind Recess				White Beige Graphite	Free Hanging Guide wire Chrome Dome Nickel Dome Chrome Flush Black Flush Nickel Flush	Top Face	No handle/Face Chrome /Face Chrome/Bottom Nickel/Face Nickel/Bottom	
3		Blind Recess				White Beige Graphite	Free Hanging Guide wire Chrome Dome Nickel Dome Chrome Flush Black Flush Nickel Flush	Top Face	No handle/Face Chrome /Face Chrome/Bottom Nickel/Face Nickel/Bottom	

Blind or Recess.

- Hardware width (Z) of blind is fabric width (X) plus 6 mm (3mm per side) allowance for end caps. If recess is specified an additional allowance for installation / clearance is made of 2mm per side, resulting in fabric width 10mm less than recess (5mm each side).
- The overall blind drop Y is measured from top of headrail to bottom of moving rail. No deduction is made for either blind or recess fit.
- If not fitting in recess consider suitable overlap to minimise light bleed or gap around blind, and allow for upper and lower fixings.

Fabrics

- 20mm Classic pleated fabrics are available, with a choice of Sheer, Privacy or Blackout
- 25mm Privacy fabrics are available from the Honeycomb range.

Blackout Honeycomb is not available on this blind.

Please see the Online fabric collection

Maximums and minimums

	Min	Max
Width (X)	280mm [11"]	2000mm [78 3/4"]
Drop (Y)	150mm [5 7/8"]	2000mm [78 3/4"]